

Cold Water Pressure Washers

Cold Water Engine Drive Features Include:

- Gas or diesel engine drive
- Triplex plunger, oil bath, positive displacement water pump, direct drive, 5.5 models with gear reduction
- 12-volt DC electrical system
- Trigger type, insulated pistol grip shut-off gun with variable pressure lance
- 3/8" x 50' (0.95cm x 15.25m) high-pressure hose with quick couplers
- Quick couple nozzles of 0-, 15-, & 25-degree angles
- Detergent injector
- Includes pressure gauge, pressure relief valve, thermal relief valve, and water back flow prevention
- 3.5 model with two-wheel cart; 5.5 models with skid with overhead lift points

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Motor HP/KW	Drive Type
12 DC				11 / 8.6	Direct

Performance

	Flow		Pressure	
	GPM	LPM	PSI	BAR
Pressure Washer	3.5	13.2	3000	206.7

Fuel Supply

Fuel Type	Fuel Usage
Gasoline	0.92 GPH

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
37	940	29	737	47	1194
Weight			185 (lbs), 84 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice