C5.0E3000-50

Cold Water Pressure Washers

Cold Water Washer Features Include:
• Belt driven triplex plunger, oil bath, positive displacement water pump rated to 140°F (60°C) inlet water with thermal relief valve
• TEFC motor with thermal overload protection
• Trigger type, pistol grip shut-off gun with double barrel lance
• 3/8” x 50’ (0.95cm x 15.25m) high-pressure hose with quick couplers
• Quick couple nozzles of 0-, 15-, & 25-degree angles
• NEMA 4 electrical enclosure
• ETL certified to UL1776, UL 508A, CSA22.2 No. 68 and CSA-C22.2 No. 14 Standards
• Meets the National Electric Code (NEC), the Canadian Electric Code (CEC), and complies with OSHA Regulation 1910.303(a)
• **Explosion-Proof models only** – ETL certified to UL1203, CSA22.2 No. 25 and 30 standards. For use in Class I, Division 1, Group C & D and Class II, Division 1, Group F & G hazardous locations. Includes explosion-proof sealed cast aluminum electrical enclosure, explosion-proof motor, and conduit.



Electrical & Mechanical Information					
Voltage	Phase	Hertz	Operating Current Amps	Motor HP/KW	Drive Type
380/400/415	3	50	32/29/28		Belt

Performance				
	Flow		Pressure	
	GPM	LPM	PSI	BAR
Pressure Washer	5	18.9	3000	206.7

Fuel Supply	
Fuel Type	Fuel Usage

Weight & Dimensions					
Length		Width		Height	
in	mm	in	mm	in	mm
31	787	44	1118	47	1194
Weight		365 (lbs), 166 (kgs)			

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice