

Cold Water Pressure Washers

Cold Water Washer Features Include:

- Belt driven triplex plunger, oil bath, positive displacement water pump rated to 140°F (60°C) inlet water with thermal relief valve
- TEFC motor with thermal overload protection
- Trigger type, pistol grip shut-off gun with double barrel lance
- 3/8" x 50' (0.95cm x 15.25m) high-pressure hose with quick couplers
- Quick couple nozzles of 0-, 15-, & 25-degree angles
- NEMA 4 electrical enclosure
- ETL certified to UL1776, UL 508A, CSA22.2 No. 68 and CSA-C22.2 No. 14 Standards
- Meets the National Electric Code (NEC), the Canadian Electric Code (CEC), and complies with OSHA Regulation 1910.303(a)
- **Explosion-Proof models only** - ETL certified to UL1203, CSA22.2 No. 25 and 30 standards. For use in Class I, Division 1, Group C & D and Class II, Division 1, Group F & G hazardous locations. Includes explosion-proof sealed cast aluminum electrical enclosure, explosion-proof motor, and conduit.



Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Motor HP/KW	Drive Type
380/400/415	3	50	40		Belt

Performance

	Flow		Pressure	
	GPM	LPM	PSI	BAR
Pressure Washer	5	18.9	5000	344.5

Fuel Supply

Fuel Type	Fuel Usage

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
36	787	49	1118	47	1194
Weight			425 (lbs), 193 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice