

All Electric Pressure Washers & Steam Cleaners

All-Electric Features Include:

- Tankless design requires no preheating and provides a continuous discharge temperature
- Sioux patented encapsulated electric heating element with Incoloy sheathed element rods in a hydrostatically tested vessel
- NEMA 4 watertight enclosure. On/Off controls for the electric motor and heating element with indicator lights. Circuit breakers for the motor, primary transformer, and heating element circuits
- TEFC motor with thermal overload protection
- Triplex, ceramic plunger pump with stainless steel valves
- High pressure relief valve, high temperature limit switch, water flow switch, thermometer, and pressure gauge. Hour meter and shutdown timer
- Adjustable digital temperature control
- Includes trigger shut-off gun and lance, quick couple wash tips of 0-, 15-, and 25-degree angles and either a 2" or 3" stainless steel fan nozzle
- Stainless steel float tank
- 50' hose (15.25m)
- Detergent metering valve
- Caster mount, powder coat paint finish, carbon steel frame with lifting eyes
- ETL certified to UL1776, UL 508A, CSA22.2 No. 68 and CSA-C22.2 No. 14 Standards
- Meets the National Electric Code (NEC), the Canadian Electric Code (CEC), and complies with OSHA Regulation 1910.303(a)



Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Heating Element KW	Motor HP / KW	Pump RPM	Drive Type	Explosion Proof Rated
380/400/415	3	50	50/52/44	30/33.2/28.4	1.5 / 1.12	1,450	Direct	No

Performance

	Flow		Pressure		Temp Rise*	
	GPM	LPM	PSI	BAR	°F	°C
Pressure Washer	2	7.6	1000	68.9	99	110
Steam Cleaner	0.8	0.85	250	17.2	260	145
*320°F (160°C) is the high temperature limit						

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
44	1118	17	431.8	29	736.6
Weight			310 (lbs), 141 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice