

SIoux**EHS1.0XD**

- 90% Efficiency
- Standard BTU ratings are 1.0, 1.7, 3.0, or 5.0 Million BTU/Hr heat output
- Standard primary electricals are 115/1Ph/60Hz and 460V/3Ph/60Hz
- Available with Oil, LP, Natural Gas or Combination burners
- Touch screen interface
- Remote monitoring and operation with Sioux Sentinel

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Heat Input BTU/Hr
115/230	1	60	7/4	1,090,000

Connections

Water Inlet	Water Outlet	Fuel Inlet	Flue Size
1-1/4" Flange	1-1/4" Flange	1/4" NPT	12"

Performance

Heat Output BTU/Hr	Boiler HP	Minimum Water Flow Rate	Maximum Water Flow Rate	Max Achievable Water Tank Temperature
1,000,000		15	50	300

Fuel Supply

Fuel Type	Fuel Usage
Diesel	8.6 GPH

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
86	2184	38	965	61	1549
Weight			1850 (lbs), 840 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice