

SIoux**EHS3.0XC**

- 90% Efficiency
- Standard BTU ratings are 1.0, 1.7, 3.0, or 5.0 Million BTU/Hr heat output
- Standard primary electricals are 115/1Ph/60Hz and 460V/3Ph/60Hz
- Available with Oil, LP, Natural Gas or Combination burners
- Touch screen interface
- Remote monitoring and operation with Sioux Sentinel

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Heat Input BTU/Hr
230/460/575	3	60	8/4/3	3,260,000

Connections

Water Inlet	Water Outlet	Fuel Inlet	Flue Size
2" Flange	2" Flange	2" NPT - Gas 3/8" NPT Diesel	18"

Performance

Heat Output BTU/Hr	Boiler HP	Minimum Water Flow Rate	Maximum Water Flow Rate	Max Achievable Water Tank Temperature
3,000,000		40	115	300

Fuel Supply

Fuel Type	Fuel Usage
Combo	

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
175	4445	50	1270	71	1803
Weight			5650 (lbs), 2563 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice