

SIoux**H3.8N2000****Dakota II Pressure Washers & Steam Cleaners****Dakota II Fuel Fired Features Include:**

- 3Triplex plunger, oil bath, positive displacement water pump
- TEFC motor with thermal overload protection
- Oil (diesel), natural gas, or propane fired burner
- 1/2" Schedule 80 pipe heating coil
- Trigger type, insulated pistol grip shut-off gun with 48" lance
- 50' (15.25m) high-pressure hose with quick couplers
- Quick couple nozzles of 0-, 15-, & 25-degree angles, round steam nozzle and 3" fan steam nozzle
- Upstream detergent metering valve
- Adjustable digital temperature control
- Flow switch, high temperature limit, pressure relief valve, thermal relief valve, rupture disc, and stainless-steel float tank with inlet water back flow prevention
- NEMA 4 electrical enclosure
- Frame with forklift pockets and 4-point overhead lift points
- Self-certified to UL 60335-2-79, CSA E60335-2-79 and complies with OSHA Regulation 1910.303(a)

**Electrical & Mechanical Information**

Voltage	Phase	Hertz	Operating Current Amps	Heat Input BTU/Hr	Motor HP/KW	Pump RPM	Drive Type	Flue Size
230	1	60	26	320,000	5 / 3.73		Direct	6"

Performance

	Flow		Pressure		Temp Rise*	
	GPM	LPM	PSI	BAR	°F	°C
Pressure Washer	3.8	14.4	2000	138	140	78
Steam Cleaner	1.9	7.2	500	34	260	145

*Temperature rise is based on 60°F (15°C) inlet temperature;
320°F (160°C) is the high temperature limit

Fuel Supply

Fuel Type	Fuel Tank Size	Fuel Usage
		320 CFH

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
48	1219	30	30	37	762
Weight		680 (lbs), 309 (kgs)			

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice