



SF-100D-ENC

Steam-Flo

Steam-Flo Features Include:

- Maximum steam pressure - 15 PSI
- Maximum steam temperature - 250°F
- Redundant safety controls: auto reset pressure switch, manual reset pressure switch, ASME pressure relief valve, pressure gauge, water feeder with level switch, manual reset level switch, check valve, and inlet water screens
- Full steam production within 5-10 minutes of start-up
- Continuous supply of steam
- NEMA 4 electrical enclosure
- Safety Standards: UL-508A/CSA C22.2#14; ASME Section IV, CRN* (CRN not currently available for all-electric models SF3.8-E & SF11-E)



* Inlet water pressure requirement - Minimum 40 PSI, Maximum 150 PSI

* Inlet water supply should be minimum 1.5X usage

* Maximum inlet water temperature 120°F (49°C)

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps
230	1	60	12

Performance

Boiler HP	Heat Input BTU/Hr	Steam Output Lbs/Hr	Max Steam Pressure PSIG	Max Steam Temperature °F
100	4,000,000	3,450	15	250

Connections

Water Inlet	Steam Outlet	Fuel Inlet	Flue Size
3/4" Garden Hose	6" Flange	3/8" Hose Barb	20"

Vessel Details

Total Boiler Volume	Operating Boiler Volume	Heat Transfer Surface	Water Usage
828 Gallons	652 Gallons	533 sq ft	6.9 GPM

Fuel Supply

Fuel Type	Fuel Usage	Tank Size
Diesel	30 GPH	(2) 119 Gallons

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
481 in	12,217 mm	97 in	2,457 mm	141 in	3,571 mm
Weight			19,400 lbs (lbs), 19,400 lbs (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice