



TSC1000-1005F

Tank Skid Package Features

- Tank with a vent, tank anode, fluid level indicator, level switches for low level and makeup water.
- 2" NPT makeup water solenoid valve
- Suction diffuser on the inlet of main pump
- Inlet y-strainer on the inlet of the optional secondary pump
- NEMA 4 watertight electrical enclosure with motor starters with overloads, On/Off switches, transformer, and circuit breakers.
- Includes a single panel mounted GFCI outlet and port for plumbing the optional Sioux Clean water treatment metering pump.
- Skid with forklift pockets.
- For models with an insulated tank - enamel coated 1" nominal thickness insulation

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Main Motor HP	Secondary Motor HP
208/230/460	3	60	41/37/19	10	5

Connections

Makeup Water Solenoid	Tank Inlet Port	Tank Outlet Port	Tank Drain Port	Main Pump Outlet	Secondary Pump Outlet
2" NPT	3" Groove	3" Groove	2" NPT	3" NPT	2" NPT

Tank Information

Tank Material	Tank Size	Tank Insulation
Carbon	1000	Yes

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
124	3150	72	1829	83	2100
Weight			2650 (lbs), 1202 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice