



TSC2500-1000N

Tank Skid Package Features

- Tank with a vent, tank anode, fluid level indicator, level switches for low level and makeup water.
- 2" NPT makeup water solenoid valve
- Suction diffuser on the inlet of main pump
- Inlet y-strainer on the inlet of the optional secondary pump
- NEMA 4 watertight electrical enclosure with motor starters with overloads, On/Off switches, transformer, and circuit breakers.
- Includes a single panel mounted GFCI outlet and port for plumbing the optional Sioux Clean water treatment metering pump.
- Skid with forklift pockets.
- For models with an insulated tank - enamel coated 1" nominal thickness insulation

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Main Motor HP	Secondary Motor HP
208/230/460	3	60	27/25/13	10	0

Connections

Makeup Water Solenoid	Tank Inlet Port	Tank Outlet Port	Tank Drain Port	Main Pump Outlet	Secondary Pump Outlet
2" NPT	4" Groove	4" Groove	2" NPT	3" NPT	N/A

Tank Information

Tank Material	Tank Size	Tank Insulation
Carbon	2500	No

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
142	3607	92	2337	106	2697
Weight			4570 (lbs), 2072 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice