

SIoux**WHC1.7PC****Features Include:**

- PLC with HMI touchscreen allows for remote operation and monitoring of the system through customer's local area network
- Predictive maintenance and troubleshooting alerts help streamline maintenance
- PLC Scheduling feature will adjust operating dates, times and tank temperature set points - Also allows for integration and control of Sioux's tank skid packages (sold separately)
- Circulation pump and motor circulates water from the supply to the destination through the three pass Sch. 40 carbon steel heat exchanger
- Adjustable tank temperature control maintains desired setting
- Electrical disconnect makes power isolation for maintenance quick and easy
- Emergency stop switch for added safety
- Safety Standards: UL508A/CSA C22.2#14; ASME Section IV; Canadian Registration Number (CRN)
- Skid mount with forklift pockets for easy placement and loading/unloading
- Additional features include inlet and outlet pressure gauges, NEMA 4 electrical enclosure, inner and outer coil flow switches and temperature limits, and ASME rated relief valve.
- Models are available with Variable Frequency Drive (VFD) and modulating burner for precise outlet temperature control
- 90% efficient

**Electrical & Mechanical Information**

Voltage	Phase	Hertz	Operating Current Amps	Heat Input BTU/Hr
208/230/460/575	3	60	28/24/12/11	1,850,000

Connections

Water Inlet	Water Outlet	Fuel Inlet	Flue Size
2" NPT	2" NPT	1-1/2" NPT-Gas 3/8" NPT-Diesel	12"

Performance

Heat Output BTU/Hr	Minimum Water Flow Rate	Maximum Water Flow Rate	Max Achievable Water Tank Temperature
1,700,000	40	105	170

Fuel Supply

Fuel Type	Fuel Usage
Combo	Contact

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
109	2769	50	1270	63	1600
Weight			2660 (lbs), 1207 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2021 - Subject to change without notice