



WHC76PE-T

Features Include:

- PLC with HMI touchscreen allows for remote operation and monitoring of the system
- Sioux patented SCR advanced temperature control for precise temperature control
- Flanged Incoloy 800 sheathed heating elements
- 5 HP discharge pump and motor
- Troubleshooting alerts help streamline maintenance
- Electrical disconnect makes power isolation for maintenance quick and easy
- Emergency stop switch for added safety
- Safety Standards: UL508A/CSA C22.2#14
- Skid mount with forklift pockets for easy placement and loading/unloading
- 99% efficient

Electrical & Mechanical Information

Voltage	Phase	Hertz	Operating Current Amps	Circuit Requirement Amps
240/480/600	3	60	196/98/79	250/125/100

Connections

Water Inlet	Water Outlet	Tank Material	Tank Size Gallons
1-1/2" NPT	2" NPT	Carbon Steel	300

Performance

Heat Input BTU/Hr	Heat Output BTU/Hr	Heat Source	Heating Element kW
259,300	259,300	Electric	76

Weight & Dimensions

Length		Width		Height	
in	mm	in	mm	in	mm
61	1,549	57	1,448	76	1,930
Weight			1,480 (lbs), 672 (kgs)		

For More Info Visit sioux.com

Sioux Corporation, Copyright 2026 - Subject to change without notice